



(Specifier Note: The purpose of this guide specification is to assist the Specifier in correctly specifying Palmer Fixture high speed electric hand dryers and their installation.)

Palmer Fixture

P.O. Box 10887

Green Bay, WI 54307

Phone: 1.800.558.8678 * **Email:** info@palmerfixture.com

Website: www.palmerfixture.com

For over one hundred years, Palmer Fixture has been dedicated to providing the most competitive, value-added washroom accessories. We are constantly expanding our product lines and are looking for more ways to satisfy our customers. Through extensive research and development, Palmer Fixture Company has maintained a world wide reputation for product excellence since 1907.

SECTION 10 28 00 - HAND DRYERS

Palmer Fixture iStorm2



PART 1 - GENERAL

1.1 SECTION INCLUDES

- A. Automatic, high speed, warm-air, energy efficient self-contained electric hand dryers

1.2 RELATED SECTIONS

- A. Section 06 10 00 - Rough Carpentry: Blocking in stud partitions for mounting hand dryers
- B. Section 26 05 00 - Wiring Methods: Electrical supply, conduit, wiring, boxes, and wiring devices for hand dryers

1.3 REFERENCES

- A. ICC/ANSI A117.1-American National Standard for Accessible and Useable Buildings and Facilities

1.4 SUBMITTALS

- A. Submit in accordance with Section 01 33 00 - Submittal Procedures
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations
 - 2. Operating instructions and recommendations
 - 3. Storage and handling requirements and recommendations
 - 4. Installation methods
- C. LEED Submittals: Provide documentation of how the requirements of Credit will be met
- D. Shop Drawings: Include dimensions, method of attachment, and electrical wiring

1.5 QUALITY ASSURANCE

- A. Hand Dryers shall be provided and installed in compliance with a ICC/ANSI A117.1
- B. UL and C-UL approved and shall bare UL and C-UL labels
- C. CE approved
- D. GreenSpec® Listed

1.6 DELIVERY, STORAGE AND HANDLING

- A. Deliver dryers and components in manufacturer's original, unopened, undamaged containers with identification labels intact
- B. Store dryers as recommended by manufacturer

1.7 WARRANTY

- A. Provide manufacturer's standard limited warranty for period specified
 - 1. Warranty Period: [5] years

PART 2 - PRODUCTS

(Specifier Note: Product Information is proprietary to Palmer Fixture. If additional products are required for competitive procurement, contact Palmer Fixture for assistance in listing competitive products that may be available.)

2.1 MANUFACTURER

- A. Basis-of-Design Manufacturer: Palmer Fixture; PO BOX 10887 Green Bay, WI 54307; Phone: 920-884-8698, Fax: 920-884-8699; Toll free 800-558-8678; websites www.palmerfixture.com and www.stormdryers.com
 - 1. Substitutions: Not Permitted
 - 2. Subject to compliance with requirements, manufacturers of products of equivalent design may be acceptable if approved in accordance with Section 01 63 00 - Product Substitution Procedures

2.2 ELECTRIC HAND DRYERS

HD0983-08: Platinum, 110/120V

HD0983-16: Black, 110/120V

HD0983-17: White, 110/120V

HD0984-08: Platinum, 208/220V

HD0984-16: Black, 208/220V

HD0984-17: White, 208/220V

HD0985-08: Platinum, 277V

HD0985-16: Black, 277V

HD0985-17: White, 277V

- A. Electric Hand Dryers: iStorm Electric Hand Dryer Mounting: Surface mounted on pressed anti-rust steel back plate.

Construction: Polycarbonate ABS casing with anti-microbial scuff resistant coating on exterior surfaces. Anti-microbially integrated external plastics and seals. Tamperproof type security hex mounting screw. Water ingress protection to IP23.

Color Finish: Metallic platinum, white, or black gloss.

Filtration: 99.97 percent particulate efficiency 3 part super HEPA filter.

Operation: Touch-free infra-red (LED red) standby, infra-red (LED blue) activation.

- a. Hand dry time: 10-15 seconds
- b. Airspeed: 140-224 mph adjustable

- c. Operating airflow: 55-76 cfm
 - d. Rated Operating Noise Power: 65dB to 78db MAX
- Motor: 1HP, 400-750W; 11,000-20,000 rpm motor speed; one (1) watt standby power consumption.

Specifier Note: SELECT 110-220 option when better efficiency is desired. Standby power on the 120 V model consumes 1 W and 1 W on the 240 V model. 120 V is also a more standard voltage. COORDINATE project electrical requirements with electrical engineer.

Electrical Requirements: [110-120 V AC, 10 A, 1600 W, 50/60H.] [208-240 V AC, 5A, 1200 W, 50/60 H.]

(Specifier Note: DELETE one of the following power sources.)

- 1. Power Source: HD0983, 110/120 volt, 9.2-10 amp, 1600W
- 2. Power Source: HD0984, 208/220 volt, 4.3-5 amp, 1600W
- 3. Power Source: HD0985, 277 volt, 4.6-5 amp, 1600W

- 4. Weight: 23.8 LBS (10.79 kg)
- 5. Nominal Size: 12 43/64 inches (324mm) wide by 24 19/32 (590mm) inches high by 7 9/32 (184mm) inches deep

(Specifier Note: Indicate mounting height on DRAWINGS or designate as part of specification; do not indicate mounting heights in both specifications and drawings. DELETE one of the following two paragraphs.)

- 6. Mount dryers at heights indicated on drawings
- 7. Mount at the following heights above floor surface, as measured from the bottom the dryer:
 - a. Men's Restrooms: 26.06 inches (1219 mm)
 - b. Women's Restrooms: 23.08 inches (1143 mm)
 - c. Children Ages 11-18: 9.52 inches (1067 mm)
 - d. Children Ages 3-10: 15.08 inches (940 mm)
 - e. Restrooms for Persons with Physical Disabilities: 13.625 inches (902 mm)

PART 3 - EXECUTION

3.1 GENERAL

- A. Install hand dryers in accordance with manufacturer's installation guidelines and recommendations

3.2 PREPARATION

- A. Verify substrates have been properly prepared

- B. Coordinate location and installation of electric hand dryers with blocking and other fixtures
 - 1. Verify dryers will be located at least 2 feet apart
 - 2. Verify dryers will be located at least 12 inches from side of washbasin
 - 3. Verify dryers will be located at least 18 inches above any projection which may interfere with operation of automatic sensor
- C. Coordinate location and requirements for power supply, conduit, disconnect switches and wiring

3.3 INSTALLATION

- A. Install hand dryers level, plumb, and firmly anchored in locations and at heights indicated
- B. Install hand dryers using manufacturer recommended fasteners for each substrate

3.4 PROTECTION

- A. Protect installed hand dryers after installation from damage during construction. If damage occurs, remove and replace damaged unit as required to provide units in their original, undamaged condition.

END OF SECTION